WESTINGHOUSE

WVE6515SD 60CM MULTI-FUNCTION 7 OVEN

PRODUCT FACTSHEET
Built in Australia

The Westinghouse WVE6515SD is a premium 60cm electric built-in single oven engineered for Australian families. Featuring a generous 80L gross capacity, fast heat-up technology, dark fascia styling with mark-resistant stainless steel, and 7 versatile cooking functions, it delivers dependable culinary performance and sleek modern aesthetics.

KEY FEATURES & HIGHLIGHTS

Fast Heat Up Mode
Designed for busy lifestyles, reducing pre-heat waiting time so cooking starts sooner.

Programmable Touch Timer
Sleek 3-button digital LED control panel featuring minute minder, cook time, and auto off.

Cooler Touch Glass Door
Multi-layer glazed glass door maintains lower outer temperatures for kitchen safety.

Easy Guide Side Racks
Smooth side rack guides allow effortless, stable shelf placement across 5 positions.

TECHNICAL SPECIFICATIONS

Parameter	Specification Standard
Gross / Useable Capacity	80 Litres Gross / 72 Litres Useable
Oven Functions (7)	Fan Forced, Traditional Bake, Fan Grill, Grill, Pizza, Defrost, Rapid Heat
Exterior Finish	Mark-Resistant Stainless Steel with Dark Glass Fascia
Controls	Rotary Control Knobs & 3-Button LED Touch Timer
Cavity Enamel	Pyrolux High-Temperature Easy-Clean Enamel
Electrical Connection	3.1 kW Connected Load | 12.9 A Max Rating (Hardwired)
Door Construction	Drop-down, Removable Door & Inner Glass Panes (Cool Door)
Included Accessories	2 x Chromed Wire Shelves, Baking Tray, Oven/Grill Pan, Grill Insert, Side Racks
Country of Origin	Designed & Manufactured in Adelaide, Australia

DIMENSIONS & CABINETRY CUTOUT GUIDE



PHYSICAL & CUTOUT DIMENSION SPECIFICATIONS

Dimension Category	Product Size (mm)	Minimum Cutout Required (mm)
Overall Height	597 mm	590 mm (Underbench / Wall)
Overall Width	596 mm	560 mm
Overall Depth	573 mm (including 23mm fascia)	560 mm (internal clear depth)
Fascia Panel Depth	23 mm	N/A (Sits proud of cabinet face)
Flush Fit Cutout	600 mm (H) × 600 mm (W)	For full flush architectural installation
Proud Fit Cutout	590 mm (H) × 565 mm (W)	Standard Australian cabinetry reveal

INSTALLATION REQUIREMENTS & CLEARANCE NOTES

- **Electrical Requirements:** 220–240V AC, 50Hz single-phase connection. Maximum current rating is **12.9 Amps** with a total connected load of **3.1 kW**. This unit requires hardwired installation performed by a licensed electrician.
- **Ventilation Clearance:** Ensure a minimum clearance gap of 45mm is maintained at the rear bottom of the cavity to allow adequate cooling air intake.
- **Mounting:** Unit must be securely fastened to surrounding cabinetry using the supplied screws inserted through the front frame mounting holes.

USER MANUAL: OPERATING INSTRUCTIONS

Before using your oven for the first time, perform an initial burn-off by running the empty oven on **Traditional Bake at 200°C for 45 minutes** to eliminate manufacturing oils and residues.

COOKING FUNCTION SELECTOR

Function Symbol	Mode Name	Recommended Application
Fan Forced	Fan Forced Cooking	Multi-shelf baking, batch cooking, and general roasting at uniform heat.
Traditional	Traditional Bake	Single-shelf baking of delicate cakes, pastries, and slow-cooked casseroles.
Fan Grill	Fan-Assisted Grill	Thick cuts of meat, sausages, and poultry; locks in moisture with even browning.
Grill	Full Electric Grill	Quick toast, browning top casseroles, and small thin cuts of meat.
Pizza	Pizza Mode	High bottom heat with fan circulation for crispy bases and golden toppings.
Rapid Heat	Fast Pre-Heat	Quickly brings cold oven up to target set temperature prior to baking.
Defrost	Air Defrost	Circulates room temperature air to safely thaw delicate foods without heat.

CARE, MAINTENANCE & SAFETY GUIDELINES

- **Cleaning Enamel Cavity:** Wipe down internal walls after every use with warm soapy water and a microfiber cloth. Avoid harsh abrasive pads or caustic spray cleaners.
- **Door Glass Maintenance:** The inner door glass panels can be unclipped easily for cleaning. Ensure glass panels are completely dry and reinstalled correctly before operating.
- **Timer Setup:** Use the 3-button touch LED panel to set cook times or minute minders. Auto-off automatically turns heating elements off upon duration completion.

> **IMPORTANT SAFETY PRECAUTION:** Accessible parts become hot during use. Always keep young children away from the unit during baking or grilling. Always isolate the electrical supply circuit prior to replacing the light bulb or conducting servicing.